




DESCRIPTION

Parfaitement adapté aux enceintes de la série DZR, le DXS18-XLF est un caisson de graves de type bass-reflex offrant une réponse étendue dans les fréquences basses, produisant un niveau de pression acoustique maximal de 136 dB SPL avec une clarté remarquable.

Caisson de graves 18" avec bobine 4"

Niveau de pression acoustique maximal 136 dB SPL, réponse en fréquence de 30Hz à 150Hz

Amplification classe D 1600W

DSP 96kHz pour un son haute résolution avec une latence ultra faible

Nombreuses fonctions DSP, chargement de préréglages, égalisation paramétrique, délai et routing accessibles intuitivement via l'écran LCD

Traitement D-XSUB et mode cardioïde, circuits de protection extrêmement fiables

Coffret en multiplis résistant avec revêtement Polyurea durable

Housse (SPCVR-DXS18X) et roulettes (SPW-1) optionnelles
Speaker type
Powered Subwoofer, bass-reflex

Frequency range (-10dB)
30Hz - 150Hz

Coverage area
-
LF : 18 Cone, 4 Voice Coil, Ferrite magnet
MF : -
HF : -

Crossover
-
Internal : 96kHz and FIR Filter

A/D D/A Converters
96kHz AD/DA

Maximum output level (1m; on axis)
136dB SPL *1
Dynamic : 1600W *2
Continuous : 1230W
Analog I/O : Analog IN: Combo x2, Line level (Maximum +24dBu), Input impedance 20kΩ, Analog OUT: XLR3-32 x2, CH1/2: THRU or DSP OUT
Others : USB2.0 Host 5V 500mA for USB memory DATA storage/load
AC : IEC AC inlet x1 (V-Lock)

Amplifier class
Class-D

Cooling
Fan cooling, Variable speeds

Power consumption
40W (Idle), 180W (1/8)

Handle
Aluminium die-cast, Side x2

Rigging
-
W : 550 mm (21.7)
H : 657 mm (25.9) (with rubber feet)
D : 720 mm (28.3)

Net weight
48.9kg (107.8lbs)

Options
Cover: SPCVR-DXS18X, Caster: SPW-1

Others
Enclosure Material, Finish, Color: Plywood, Durable Polyurea Painting, Black

Floor Monitor Angle
-

Pole socket
Φ35 mm (depth 80mm), M20 Threaded (depth 25mm)

RÉFÉRENCE MARQUE : CDXS18XLF **INFORMATIONS FABRICANT**